



Thermal Transfer Ribbon Technical Data Sheet



Peak-Ryzex Performance Ultra Premium

Product Description

Peak-Ryzex has the most elite resin ribbon offering in the industry. Performance Ultra Premium's extensive label adaptability and high print speed capability makes it the most diverse resin of its kind. It outperforms the competition in abrasion and solvent resistance, uses less print energy and is designed with Peak-Ryzex's standard anti-static and backcoat properties to protect printheads and extend printhead life. And, like all of Peak-Ryzex's ribbons, Ultra Premium produces dark, dense images for improved scan rates.

Performance Characteristics

- Excellent print quality at high speeds using less print energy
- Extreme durability and solvent resistance
- Extensive label adaptability expanding application options
- UL recognized/CSA approved
- Unbeatable for dark, dense images and improved scan rates
- Specially formulated backcoating for printhead protection
- Anti-static for easy handling and extended printhead life

Recommended Applications



AGENCY



ASSET TRACKING



AUTOMOTIVE



CHEMICAL DRUM



ELECTRONIC COMPONENT



EXTREME ENVIRONMENT



FLEXIBLE PACKAGING



HAZARDOUS



OUTDOOR



PHARMACEUTICAL



PRODUCT ID



RFID



SECURITY



SHELF

Recommended Substrates

Polypropylene, polyethylene, polyolefin, vinyl, polyester

Contact Us

Our customer call center is available 24 hours a day, 7 days a week for customer service requests

To place a service call:

☎ 1-888-275-7325

✉ service@peak-ryzex.com

Peak-Ryzex Performance Ultra Extreme

Ribbon Properties

Description	Result	Test Method
Ink	Resin	
Color	Black	Visual
Total Thickness	6.0 ± 0.5μ	Micrometer
Base Film Thickness	4.8 ± 0.3μ	Micrometer
Ink Thickness	1.2 ± 0.2μ	Micrometer
Ink Melting Point	86°C (187°F)	Differential Scanning Calorimeter

Durability of Printed Image

Label Stock: Top-coated Polyester

Print Speed: 6 IPS

Description	Result	Test Method
Print Density	> 1.80	Densitometer
Smudge Resistance	A*	Colorfastness Tester - 100 Cycles @ 500 Grams with Cotton Cloth
Scratch Resistance	A*	Colorfastness Tester - 50 Cycles @ 200 Grams with Stainless Steel Pointed Tip

*American National Standard Institute (ANSI) Grade Levels A, B, C, D, and F, where A is excellent, B is above average, C is average, D is below average, and F is poor.

Conversion Chart

Millimeters (mm) to Inches = mm ÷ 25.4	Inches to Millimeters (mm) = Inches × 25.4
Meters (m) to Feet (ft) = m × 3.2808	Feet (ft) to Meters (m) = Feet ÷ 3.2808
C° to F° = (1.8 X C°) + 32 = F°	F° to C° = (F° - 32) ÷ 1.8 = C°
Thousand square inches (MSI) to m ² = MSI X 0.645	m ² to MSI = m ² ÷ 0.645

PEAK-RYZEX™

Peak-Ryzex, Inc.

10330 Old Columbia Road, Columbia, Maryland 21046 • USA • 800-926-9212

info@peak-ryzex.com | www.peak-ryzex.com

© 2017 Peak-Ryzex, Inc. All rights reserved.